

Dual Breakaway Series

No More Costly Clean-ups!



- ✓ Reduces repairs to power units
- ✓ Reduces spillage of hydraulic fluid and costly cleanup
- ✓ Reduces driver downtime
- ✓ Reduces customer aggravation
- ✓ Great for high profile locations – airports, ports, business parks, medical facilities

These Flat Face Couplings are the “Green Standard” for the most demanding hydraulic compactor applications. Built to perform where a dripless connection is required, and a breakaway capability is needed. We have combined technologies to address challenges related to the compactor markets.

Engineering features include: Dual axis breakaway system, dripless connectors for no environmental impact, and connect under residual pressure capability when used with APM Series nipples.

The Dual Breakaway Series increases productivity, lowers operating costs, and reduces downtime by helping to overcome operator errors and the environmental impact of hydraulic connectors.

- Size Range: 3/8" thru 5/8"
- Port Options: NPT, SAE
- Dual axis swivel to release connections in multiple directions.
- Connect under residual pressure with APM nipple.
- Robust mounting bracket.
- Up to 4500 psi operating pressure.
- Flat face valve offers leak-free connection.
- Circuit contamination reduced.

• P# **IP CO-DUAL BREAKAWAY KIT**

INCLUDES:

- Dual Swivel Breakaway with Female 1/2" 3/8"
- Coupler M.APM 13 1/2" NPT
- Coupler M.APM 9 1/2" NPT



P# **IP CO-DUAL BREAKAWAY**

IP IMPACT PLASTICS

info@impactinnovates.com

Phone: 877-454-3748 | Text: 847-426-3831